







NOTES:

- 1) MATERIAL -5: AISI 304/316 ANNEALED STAINLESS STEEL SHEET 0.063 THICK
PER MIL-S-5059 OR AMS 5513 (304) OR AMS 5524 (316)
OR ASTM A240 OR ASME SA240
REF DART SPEC. M304S16GA
- 7: AISI 304/316 ANNEALED STAINLESS STEEL SHEET 0.188 THICK
PER MIL-S-5059 OR AMS 5513 (304) OR AMS 5524 (316)
OR ASTM A240 OR ASME SA240
REF DART SPEC. M304S7GA
- 2) FINISH: POWDER COAT GREY SANDTEX (4.3.5.6) PER DART QSI 005 4.3
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N "D5160-X" AND B/N BXXXXX
PER DART QSI 044 6.7
- 7) WEIGHT -5: 0.12 lbs
-7: 0.34 lbs

PRELIMINARY ISSUE

DESIGN	AJS	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	AJS		
CHECKED	CP	DRAWING NO.	REV. A3
MFG. APPR.	DD	D5160	SHEET 3 OF 3
APPROVED		TITLE	SCALE
DE APPR.		SHEET METAL PARTS 350 SEAT	NTS
DATE	14.09.25	COPYRIGHT © 2014 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	